

Small Boat Black water system cleaning instructions.

What product do I use?

- Although there are many odor control products on the market today, none of them actually clean the system itself. Only **Sew Clean™** removes the uric scale and bacteria that forms in the systems lines.

How much Sew Clean™ do I need?

- To determine how much **Sew Clean™** you need, simply measure the length and diameter of the different piping found on the system and cross-reference this data with the Pipe Gallonage Chart below.

<i>Diameter inches</i>	<i>Gallon per feet</i>
1"	0.04
1 1/4"	0.08
1 1/2"	0.10
2"	0.16
3"	0.37



When to use Sew Clean™ ?

- As a general rule of thumb, cleaning your black water system once every three years is considered good preventative maintenance. This is even more important when salt water is used as flushing water.
- If you notice a smell, blockage or a flow problem, chances are uric scale is to blame.

Cleaning Instructions:

- Inspect the system's piping to make sure it is in good condition (no holes caused by corrosion).
- Measure the length and diameter of the different piping found on the system and cross-reference this data with the Pipe Gallonage Chart above.
- Once the system's liquid capacity is obtained, close all valve leading to the holding tank, so as to fill the piping and not the tank. If no valves are present, the system will somehow need to be blanked off.
- Fill the system by starting with the highest head to the lowest head.
- Once the system is full, let the solution work for a minimum of 6 hours.
- Reopen isolating valve and flush each head thoroughly.

Distributed by:
ProActive Marine
0434 496 600
www.proactivemarine.com.au

ProActive Marine
www.proactivemarine.com.au
ph: 0434 496 600